

# NVIDIA QUADRO FX 3450

# The Definition of Performance. The Standard for Quality.

**NVIDIA Quadro® FX 3450** is the industry's leading high-end workstation solution for CAD, DCC and scientific applications.

NVIDIA Quadro FX 3450 features outstanding performance and precision, with a revolutionary new architecture that increases raw geometry and fill rate performance over previous generation products and delivers up to 4x the hardware pixel read-back performance, with support for 256MB ultra-fast GDDR3 memory. NVIDIA Quadro FX 3450 also features support for NVIDIA® SLI™ (Scalable Link Interface) technology. NVIDIA Quadro FX 3450 offers a new level of interactivity for engineers and designers enabling unprecedented performance, features and photorealistic image quality leading to shorter production cycles and faster time-to-market.

The NVIDIA Quadro family delivers on the promise of the industry's fastest PCI Express workstation graphics solutions. Featuring NVIDIA Quadro FX 4500 at the ultra-high end, NVIDIA Quadro FX 3450 and FX 3400 at the high end, NVIDIA Quadro FX 1400 in the mid range, and NVIDIA Quadro FX 540 at the entry level, NVIDIA Quadro provides the ultimate in quality, precision,



performance, and programmability. CAD and DCC applications acquire a new level of interactivity by enabling unprecedented capabilities in programmability and precision. For the first time, styling and

production rendering become integral functions of the design workflow, shortening the production process and enabling faster time to market.

## PRODUCT SPECIFICATIONS

#### **Product Name**

# **NVIDIA Quadro FX 3450**

Form Factor	ATX, 4.38" x 8.0"		
Framebuffer Memory	256MB GDDR3		
Memory Interface	256-bit		
Memory Bandwidth	32.0 GB/sec.		
Max Power Consumption	82W		
Graphics Bus	PCI Express x16		
Display Connectors	DVI-I, DVI-I, Stereo		
Dual Link DVI	Yes (1)		
Auxiliary Power Connectors	Yes (1)		
Number of Slots	1		
Thermal Solution	Active Fansink		
Genlock/Framelock	No		
SLI Support	Yes		

## **NVIDIA QUADRO FX 3450**

#### **FEATURES**

#### **BENEFITS**

Highest Workstation Application Performance	Next-generation architecture enables over 2x improvement in geometry and fill rates with the industry's highest performance for professional CAD, DCC, and scientific applications			
Unmatched Color Precision	Full 128-bit precision graphics pipeline enables sophisticated mathematical computations to maintain high accuracy, resulting in unmatched visual quality. Full IEEE 32-bit floating point precision per color component (RGBA) delivers millions of color variations with the broadest dynamic range			
Next-generation Vertex and Pixel Programmability	NVIDIA Quadro FX 3450 graphics boards introduce infinite length vertex programs and dynamic flow control, removing the previous limits on complexity and structure of shader programs. With full support for Shader Model 3.0, NVIDIA Quadro FX 3450 delivers sophisticated effects never before imagined for real-time graphics systems			
Unparalleled Subpixel Precision	12-bit subpixel precision delivers high geometric accuracy, eliminating sparkles, cracks, and other rasterization anomalies			
Hardware-Accelerated Pixel ReadBack	Greater than 2.4GB/sec., pixel read-back performance delivers massive host throughput, more than 4x the performance of previous generation graphics systems			
Rotated-Grid FSAA (Full Scene Antialiasing)	RG FSAA sampling algorithm introduces far greater sophistication in the sampling pattern, significantly increasing color accuracy and visual quality for edges and lines, and reducing "jaggies" while maintaining performance			
High-Precision Dynamic-Range (HPDR) Imaging Technology	Sets new standards for image clarity and quality through 32-bit per component floating point capabilities in shading, filtering, and texturing. Enables unprecedented rendered image quality for visual effects processing			
SLI Support	Designed for PCI Express, the NVIDIA Scalable Link Interface technology enables intelligent and transparent scaling of professional application performance			
Single Dual-Link Digital Display Connector	Dual-link TMDS transmitters support ultra-high-resolution panels (up to 3840x2400 @ 24Hz)—which result in amazing image quality producing detailed photorealistic images			

	Memory Size	Memory Interface	Relative Perf*	SLI Support	Dual-Link DVI
NVIDIA Quadro FX 4500	512MB	256 bit	3.5	Yes	Yes (2)
NVIDIA Quadro FX 3450	256MB	256 bit	2.5	Yes	Yes (1)
NVIDIA Quadro FX 1400	128MB	256 bit	1.9	Yes	-
NVIDIA Quadro FX 540	128MB	128 bit	1.0	No	-

\*based on US SPECviewperf

## **PRODUCT SPECIFICATIONS**

## **Supported Operating Systems**

- Microsoft® Windows® XP
- Microsoft Windows 2000
- Linux® Full OpenGL® implementation, complete with NVIDIA and ARB extensions
- AMD64, Intel EM64T

## NVIDIA Quadro FX 3450 Architecture

- 128-bit color precision
- 65,536 fragment instruction
- 65,536 vertex instruction
- 3D volumetric textures
- Single-system powerwall
- 12 pixels per clock rendering engine
- Hardware accelerated antialiased points and lines
- Hardware OpenGL overlay planes
- Hardware accelerated two-sided lighting
- Hardware accelerated clipping planes

- 3rd-generation occlusion culling
- 16 textures per pixel in fragment programs
- Window ID clipping functionality
- Hardware accelerated line stippling

## **Shading Architecture**

- Fully programmable GPU (OpenGL 2.0/DirectX 9.0c class)
- Long fragment programs (up to 65,536 instructions)
- Long vertex programs (up to 65,536 instructions)
- Looping and subroutines (up to 256 loops per vertex program)
- Dynamic flow control
- Conditional execution

## **High Level Shader Languages**

- Optimized compiler for Cg and Microsoft® HLSL
- OpenGL 2.0 and DirectX 9.0c support
- Open source compiler

## **High-Resolution Antialiasing**

- 12-bit subpixel sampling precision enhances AA quality
- Rotated-grid full-scene antialiasing (RG FSAA)
- 8x FSAA dramatically reduces visual aliasing artifacts or "jaggies" at resolution up to 1920x1200

## **Display Resolution Support**

- Dual Link DVI-I output-drives digital displays at resolutions up to 3840x2400 @ 24Hz
- Single Link DVI-I output drives digital displays at resolutions up to 1920x1200 @ 75Hz
- Internal 400 MHz DACs two analog displays up to 2048x1536 @ 75Hz each

### **nView Architecture**

 Advanced multi-display desktop and application management seamlessly integrated into Microsoft Windows



Where to buy NVIDIA Quadro

**NVIDIA Quadro** is available through many OEM partners. Please visit **www.nvidia.com/page/workstation.html** for the latest list of partners.

NVIDIA Corporation | 2701 San Tomas Expressway | Santa Clara, CA 95050 | T 408.486.2000 | F 408.486.2200 | www.nvidia.com

©2005 NVIDIA Corporation. All rights reserved. NVIDIA, the NVIDIA logo, and NVIDIA Quadro are trademarks or registered trademarks of NVIDIA Corporation. All company and product names are trademarks or registered trademarks of the respective owners with which they are associated. Features, pricing, availability, and specifications are all subject to change without notice.